

6280HD Gladiator®

HYDRAULIC WALK-BEHIND SCRAPER



Features

The 6280HD removes the worst of today's hard and soft goods, such as ceramic tile, wood floors, thin-set, sheet vinyl, linoleum, and more. Its compact design makes it ideal for use in confined spaces, while the side slide weights add extra head pressure when forward and improved traction when moved over the back wheels.

- A.** Ergonomically designed, adjustable-position hand grips; hydraulic forward drive; self-propelled reverse drive; variable speed, 10 to 30 feet per minute; optional manual drive with removal of drive pins; system for throttle/speed control and smooth transitions
- B.** Six handle positions for work under racks and in other confined areas; collapses to save space during transport and storage
- C.** Self-contained, limited-maintenance hydraulic fluid
- D.** Tie-down bail
- E.** Secure-mount side slide weights adjust scraper-head pressure; side slide weights add extra head pressure when forward and improved traction when moved over the back wheels
- F.** New rounded front-weight design better deflects loose material away from machine during use
- G.** Adjustable, self-cleaning, industrial-grade, siped wheels for improved traction over smooth or slippery surfaces; clip-pin removal allows for easy nonpowered maneuvering
- H.** Motor equipped with thermal-overload-protection circuit breaker that protects against strain or electrical overload
- I.** Oscillating action rotates the cutting blade to cut through a range of materials over various substrates; extends life cycle of machine while reducing maintenance costs
- J.** New design incorporates nine isolators for the toughest jobs

6280HD Specifications

Width	17.75"	45 cm
Max. Height	46.75"	119 cm
Height (handle folded)	29.75"	76 cm
Max. Length	49.5"	126 cm
Length (handle folded)	29.5"	75 cm
Weight	490 lb	222.3 kg
Removable Weight	78 lb front, 43 lb side	35.4 kg front, 19.5 kg side
Weight (machine only)	369 lb	167.4 kg
Speed	up to 30 ft/min	9.1 m/min
RPM	1725/1438	
Voltage	115/230	
Frequency	60/50 Hz	
HP	1.5	1.12 kW
Amps (full load)	14.7/10.5	

Meets the requirements of the Machine Directive 2006/42/EC and EMC Directive 2004/108/EC. It is CE marked.

Included with the 6280HD

- 6258: 3" x 12" self-scoring blade
- 6276-BU: 3" x 10" heavy-duty, self-scoring blade
- 6280HD-250: Transport-wheel assembly
- 7050-200: 3" x 6" premium blade
- 7050-202: 3" x 10" premium blade
- 7050-203: 3" x 12" premium blade
- 7050-204: 3" x 14" premium blade
- 6280-401B: 7/32 t-handle wrench
- 402276: 9-degree angle attachment
- 7280-2C: 30-degree angle attachment
- 7280-6: 6-inch cutting head
- 7280-12: 12-inch cutting head
- 7281-2: 2-inch carbide shank
- 7280-4: Retainer cap assembly
- Instruction manual
- One-year manufacturer's warranty on parts and labor

