

TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS

SUSTAINABILITY, ENVIRONMENT & INDOOR AIR QUALITY

	Standard	Tarkett value
Total recycled content	-	14 %
ReStart®	-	Yes
Phthalate - free	-	Phthalate-free
Floorscore certified	-	Yes
Recycled Content - Production Waste	-	14 %

CHARACTERISTICS & TECHNICAL PERFORMANCE

	Standard	Tarkett value
Type of product	-	Wall base
Length	-	120 ft (36.6 m)
Total thickness	ASTM F386	0.125 " (3.18 mm)
Profile	-	Contour 4 1/4", Recess Toeless 4 1/4", Recess Toe 4 1/4", Royale 4 1/4", Flex 4 1/4"
Length per box	-	120 ft (36.58 m)
Pattern	-	Solid
Commercial warranty	-	2 year limited
Dimensional stability	ASTM F1861 - Sec. 12.8-12.15	+/- 0.25%
Flexibility	ASTM F137	Pass
Staining of adjacent surfaces	ASTM F1861 - Sec. 12.1-12.7	Pass
Chemical Resistance	ASTM F925	Good
Light Stability	ASTM F1515	$\Delta E \leq 8.0$
Flammability	ASTM E648 (CRF)	Class 1 (≥ 0.45 W/cm ²)
Flame Spread/Smoke Density	ASTM E84	Class A < 450 smoke