


Base Sculptures™ Wall Base, Harmony

Manufacturer

Flexco Corporation
1401 East 6th Street
Tuscumbia, AL USA 35674
Phone (800) 633-3151
Fax (800) 346-9075
Email: info@flexcofloors.com,
solutions@rhctechincal.com
Internet: www.flexcofloors.com

Product Description

Flexco Base Sculptures™ wall base is a TP sculpted wall base. Base Sculptures™ wall base is incredibly durable, allowing it to stand up to a wide range of use when compared to vinyl wall base. Available in a variety of profiles that are meant to combine the look of specialty wood trims with the flexibility of a TP wall base. Base Sculptures™ wall base is designed for use in both commercial and residential wall base applications.



Profile: **Harmony (SC)**

Nominal Height: **2 5/8" (66.67 mm)**

Thickness: **3/8" (9.53 mm)**

Length: **40' Roll**

Carton Quantity: **1 Roll**

Inside and Outside Factory Corner Blocks and Mini Corners are available to match.

Technical Data

LEED® v2009 IEQ Credit 4.1: **Qualifies**
ASTM F1861-Resilient Wall Base: **Type TP, Group 2, Style D**
ASTM E648 (NFPA 253) - Critical Radiant Flux: **Class I, > 0.45 W/cm2**
ASTM E662 (NFPA 258) - Smoke Density: **Passes, <450**
ASTM E84 - Flammability: **Class A**
Acclimation Time: **48 Hours**
Storage & Acclimation Temperature: **65° - 85° F**

Adhesives* (Visit our website for complete Adhesive instructions)

WB-600 Acrylic Wall Base Adhesive
C-630 Contact Adhesive.

Installation* (Visit our website for complete Installation instructions)

Maintain the installation area, wall base, and adhesive between 65° F and 85° F for at least 48 hours before installation, during installation, and for the life of the installation. Use only on structurally sound interior wall surfaces such as dry plaster, cured drywall, exterior grade plywood, concrete and masonry that are clean, smooth, dry and structurally sound. All surfaces must be free from moisture, alkali, old adhesive, dust dirt, wax, oil, grease, loose paint or plaster, nonporous wall coverings or paints and other extraneous coatings or materials that could prevent a successful bond. Any rough or uneven surfaces may telegraph through the wall base. Refer to Base Sculptures Wall Base Installation instructions for detailed information.

Maintenance* (Visit our website for complete Maintenance instructions)

Refer to Flexco Base Sculptures Wall Base Maintenance Information for detailed Instructions.

Technical Document Support

For additional technical support, send an e-mail to solutions@rhctechincal.com

Warranty

Flexco provides a 2 year limited warranty for all Base Sculptures™ wall base. For additional information, see associated warranty documents.

**For complete adhesive, installation & maintenance instructions, visit www.flexcofloors.com*