

Ricochet™ Flexible Wall Protection

Suggested Specification



Product Details

- Durable - Superior Impact and Abrasion Resistance.
- Seamless Appearance.
- Colors Coordinate with Corner Guards and Other Wall Protection.
- 48" (1219mm) x 15 yards (13.72 meters) [widths may vary up to 52" (1321mm) based on pattern].

Options

- Rigid vinyl top trim available for half height installations.

Testing & Certification

- ASTM D1308-02 Standard Test Method for Effect of Household Chemicals on Clear and Pigmented Organic Finishes
- ASTM D4060 - Standard Test Method for Abrasion Resistance of Organic Coatings by the Taber Abraser
- ASTM D5420 - Standard Test Method for Impact Resistance of Flat, Rigid Plastic Specimen by Means of a Striker Impacted by a Falling Weight (Gardner Impact)
- ASTM E84 Standard Test Method for Surface Burning Characteristics of Building Materials
- ASTM E1428 Standard Test Method for Evaluating the Performance of Antimicrobials in or on Polymeric Solids Against Staining by Streptoverticillium Reticulum
- ASTM G21-15 Standard Practice for Determining Resistance of Synthetic Polymeric Materials to Fungi
- ASTM G22 Standard Practice for Determining Resistance of Plastics to Bacteria
- California Specification 01350 - Standard Method for The Testing And Evaluation Of Volatile Organic Chemical Emissions From Indoor Sources Using Environmental Chambers.
- NSF/ANSI 342 Sustainability Assessment for Wallcovering Product



IPC.3879/REV.8