

NCP

476

Carpet Edge



SEAL



See ngp.com for All Applicable

Certifications for this Product.




POSITIVE PRESSURE TESTED GASKETING MATERIALS FOR FIRE DOORS. FOR APPLICATION TO HOLLOW-METAL-TYPE FIRE DOORS RATED UP TO 3 HOURS AND WOOD-TYPE FIRE DOORS RATED UP TO 1-1/2 HOURS. CATEGORY J

- Aluminum Alloy 6063, T5 Temper
- 1^{7/16}" Wide x 1/2" Tall
- Smooth Top
- Weight: 0.19 Lbs./Ft.
- #10 x 1/2" FH Zinc Plated Wood Screws Included
- Mill or Dark Bronze Finish

ngp.com
1-800-NCP-RUSH

INSTALLATION INSTRUCTIONS

416



1. Cut threshold to size required.
2. Notch around door frame if desired.
3. Attach to floor surface with fasteners provided.
4. Caulk around base of threshold for moisture control.



ngp.com

1-800-NGP-RUSH

FAX: (800) 255-7874

QUOTES: quotes@ngp.com

ORDERS: orders@ngp.com

NGP MEMPHIS

4985 East Raines Road
Memphis, TN 38118

CARSON CITY

3689 Arrowhead Drive
Carson City, NV 89706