

400

Vinyl Carpet/Tile Divider Threshold



Black Vinyl

ßL

- 5 ½" Wide x 1½32" Tall
- Easy to Install Using Adhesive Like NGP RR5007BL Black RTV Silicone Rubber Construction Sealant
- Maximum Length = 73"







\*ADA Compliant when installed as illustrated between carpet



POSITIVE PRESSURE TESTED GASKETING MATERIALS FOR FIRE DOORS. FOR APPLICATION TO HOLLOW-METAL-TYPE FIRE DOORS, RATED UP TO 3 HOURS AND WOOD-TYPE FIRE DOORS, RATED UP TO 1-1/2 HOURS. CATEGORY J



ngp.com 1-800-NGP-RUSH

FAX: (800) 255-7874 QUOTES: quotes@ngp.com

## **INSTALLATION INSTRUCTIONS**



## **WARNING:**

These products can expose you to chemicals including DEHP Plasticizer, which is known to the State of California to cause cancer and/or developmental and reproductive harm. For more information, go to P65Warnings.ca.gov.

- 1. Cut threshold to size required.
- 2. Notch around door frame if desired.
- Apply solid beads of adhesive to underside of threshold legs, so when set in place the adhesive spreads to thinly cover base of all legs.
  NOTE: Adhesive must be a type

**NOTE:** Adhesive must be a type designed to bond PVC, concrete, wood, metal or other material to which threshold is being applied. NGP black silicone adhesive #RR-5007BL is specifically designed for use to install this threshold.

4. Affix threshold to desired location.





FAX: (800) 255-7874 QUOTES: quotes@ngp.com ORDERS: orders@ngp.com

## NGP MEMPHIS 4985 East Raines Road Memphis, TN 38118