




513HD

Aluminum
Heavy-Duty Threshold
 $\frac{1}{4}" \times 5"$



- ▶ Aluminum Alloy 6063, T5 Temper
- ▶ 5" Wide x $\frac{1}{4}"$ Tall
- ▶ Fluted Top
- ▶ BHMA Certified to ANSI/BHMA A156.21 Heavy Duty 10,000 Lb. Load Test
- ▶ Weight: 1.4 Lbs./Ft.
- ▶ #10 x $1\frac{1}{2}"$ FH Zinc Plated Wood Screws Included. Dark Bronze Supplied With DKB Thresholds



POSITIVE PRESSURE TESTED GASKETING MATERIALS FOR FIRE DOORS. FOR APPLICATION TO HOLLOW-METAL-TYPE FIRE DOORS, RATED UP TO 3 HOURS AND WOOD-TYPE FIRE DOORS, RATED UP TO $1\frac{1}{2}$ HOURS. CATEGORY J

ngp.com
1-800-NGP-RUSH

FAX: (800) 255-7874
QUOTES: quotes@ngp.com

THRESHOLD

INSTALLATION INSTRUCTIONS

1. Cut threshold to size required.
2. Notch around door frame if desired.
3. Attach to floor surface with fasteners provided.
4. Caulk around base of threshold for moisture control.



THE PRODUCTS
YOU COUNT ON
THE PEOPLE
YOU TRUST
— **ngp.com** —

FAX: (800) 255-7874
QUOTES: quotes@ngp.com
ORDERS: orders@ngp.com

NGP MEMPHIS
4985 East Raines Road
Memphis, TN 38118

CARSON CITY
3689 Arrowhead Drive
Carson City, NV 89706