

| | |
|---|--|
| Nominal Dimensions | 1/2" (12.7 mm) x 12' (3.7 m) or 40' (12.2 m) Lengths |
| ASTM F1861 - Resilient Wall Base | Type TP, Group 2, Style D |
| ASTM E648 (NFPA 253) - Critical Radiant Flux | Class 1, ≥ 0.45 W/cm ² |
| ASTM E662 (NFPA 258) - Smoke Density | Passes, ≤ 450 |
| ASTM E84 - Flammability | Class A |
| CAN/ULC-S102.2 - Surface Burning | 10 Flame Spread Rating 60 Smoke Developed Classification |
| ASTM F925 - Chemical Resistance | Excellent with chemicals listed in standard, Additional chemicals available via chart |
| ASTM F1515 - Light Stability | Excellent, $\Delta E \leq 8$ |
| Acclimation Time | 48 Hours, see installation instructions for details |
| Service & Storage Temperature | 65° - 85° F, see installation instructions for details |
| Sustainability Information | Contributes to LEED v4/4.1 Meets CA 01350 Requirements FloorScore Certification* NSF/ANSI 332 Certified Platinum* HPD Available* |
| Warranty | 10 Year Commercial, see warranty document for details |
| Recommended Adhesives | Excelsior WB-600, Wall Base Adhesive Excelsior C-630, Contact Adhesive |
| Technical Support | solutions@rhctechical.com |
| Product Support | sales@roppe.com |
| Technical Documentation | www.roppe.com |

*certificate or document available on website

