SAFETY GRATING


Stair Treads & Carrier Plates




Perf-O-Grip Stair Treads (standard)

All treads have welded ends for attachment to stringers.

- · Mill-galvanized steel: 11 ga and 13 ga.
- Hot rolled, pickled and oiled carbon steel: 11 ga. and 13 ga.
- 24", 30" and 36" lengths.
- 5", 7" 10" and 12" (nominal) widths.
- 11/2" and 2" channel heights.






Stair Treads (custom)

Stair Treads are also available with Traction Tread™ and other options. Consult factory with design questions.

Carrier Plates

Carrier Plates allow you to create your own custom stair treads. They are sold by the pair (2 plates = one pair).






Table for Perf-O-Grip Treads

Product	Nominal Width	"A"	"B"	"C"	"D"
2-Hole Tread	5" (127mm)	4 ¹⁵ /16" (125mm)	1 ¹ /2" (38mm)	³ /4" (19mm)	2" (51mm)
		4 ¹⁵ /16" (125mm)	2" (51mm)	1" (25mm)	2" (51mm)
3-Hole Tread	7" (178mm)	6 ¹⁵ /16" (176mm)	1 ¹ /2" (38mm)	³ /4" (19mm)	4" (102mm)
		6 ¹⁵ /16" (176mm)	2" (51mm)	1" (25mm)	4" (102mm)
5-Hole Tread	10" (254mm)	9 ¹⁵ /16" (254mm)	1 ¹ /2" (38mm)	³ /4" (19mm)	7" (178mm)
		9 ¹⁵ /16" (254mm)	2" (51mm)	1" (25mm)	7" (178mm)
6-Hole Tread	12" (305mm)	11 ¹⁵ /16" (303mm)	1 ¹ /2" (38mm)	³ /4" (19mm)	9" (227mm)
		11 ¹⁵ /16" (303mm)	2" (51mm)	1" (25mm)	9" (227mm)