KSC Standard Sills





KSC Standard Sills provide an economic solution to sill protection. Sill-Rite Standard Sills are made of durable vinyl and can be used in new constructions, retrofit/replacement, and existing homes.

KSC Standard Sills are easy to install and are superior to drywall or wood sills. Sill-Rite reduces the chances of mold and moisture damage, and provides a durable, attractive surface that is easy to clean and maintain.

KSC Standard Sills are available in several lengths and depths, and can be cut to fit most window openings. Available in two attractive profiles, KSC Standard Sills provide attractive sill protection.





KSC Standard Sills are available in two attractive profiles: Classic and Streamline

Low Maintenance

Easy to clean requires no painting or staining.

Durable

Made of cellular vinyl, KSC Premium Sills can take the abuse of outdoor elements, so it certainly can handle the indoor elements.

Protects against Moisture

Moisture from condensation and minor window leaks can lead to mold growth with drywall or MDF sills. KSC Premium Sill is a water-proof barrier that protects the sill area.

Won't Rot, <u>Peel,or Ye</u>llow

KSC Premium Sill is made of the same high quality vinyl as many windows.

Attractive Sill protection Made Easy

Moisture is a home's number-one enemy. Moisture not only damages the home, but it can also lead to dangerous mold and mildew. KSC Standard Sills help protect homes from the inevitable moisture caused by condensation on windows. When installed properly, KSC Sills helps prevent moisture from seeping into the inner wall. Not only does KSC Standard Sills protect, they are also an attractive accent to any window. KSC Standard Sills are available in the Classic profile for an elegant traditional style, or the contemporary Streamline profile.

Installation Tips

- Sills can be cut with ordinary wood cutting tools.
 Use finishing blades for a smooth cut.
- Apply a continuous bead of a weatherproof
 paintable caulk to the back edge of the sill where it
 will butt against the window. This will help ensure a
 good seal.
- Use a polyurethane construction adhesive when installing KSC Standard Sills.
- As a final step, apply a bead of paintable caulk along the sill where it butts against the wall and window.





Sills can be installed with flush ends or with extended ends.


Material: Cellular PVC **Color:** White, UV stable

Profiles: Classic and Streamline **Warranty:** Limited lifetime warranty

Durability: Will not rot, cup, split, twist, or warp **Finish:** Does not require paint but will accept paint for a custom color. For best results, prepare the surface by sanding lightly with fine sand paper. Clean the sill thoroughly and apply an acrylic latex primer. Finish with a 100% acrylic latex paint.

Care and Cleaning: Sill-Rite sills are easy to clean and require almost no maintenance. Make sure any cleaning product you use is safe for use on vinyl products.

Sizes: Standard lengths and depths as listed. Custom lengths longer than 8' are also available



Deeper Sills are achievable with our Extension Kit.