# CRACKLED





# **CRACKLED**



CRACKLED Style Name Collection Name Surface Works

Style Number 54871 Product Type **Carpet Tile** 

Construction Multi-Level Pattern Loop 100% Eco Solution Q® Nylon Fiber

Dye Method Solution Dyed Synthetic Primary Backing Strataworx Secondary Backing Traffic Rating Heavy

**Protective Treatments** SSP Shaw Soil Protection

> U.S. Metric

**Product Size** 24 in x 24 in 60.96 cm x 60.96 cm

80 ft2 Area Per Carton 7.43 m<sup>2</sup>

Pieces Per Carton 20


Gauge 1/10 in 39.37 per 10 cm Stitches 10 per in 39 per 10 cm Finished Pile Thickness 0.088 in 2.24 mm

Average Density 6545 oz/yd3

Total Thickness 0.23 in 5.84 mm Tufted Weight 16 oz/yd<sup>2</sup> 542.5 g/m<sup>2</sup>



## Recommended Installation Methods



# Performance Testing

Pill Test **Pass** Radiant Panel Class I

NBS Smoke Less than 450 Less than 3.5 kv **Electrostatic Propensity** 

CRI Greenlabel Plus GLP2671

ADA Compliance >0.6. meets the recommended static coefficient of friction

for ADA walking surfaces and accessible routes

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

## Warranties

Carpet Tile 15 year Commercial Limited Warranty with Stain and Color for StrataWorx

#### Environmental

Recycled Content

Pre-consumer - 23%, Post-consumer - 0%

Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

