

VTW VAPOR TAPE

WHITE POLYETHYLENE SEAMING TAPE



PRODUCT DESCRIPTION

Vapor Tape is a white single-sided tape that combines a heavy duty, weather-resistant polyethylene backing with an aggressive rubber adhesive. Vapor Tape offer excellent seaming capabilities for our materi~~s~~l with an “Easy Tear” feature to reduce installation time.

APPLICATIONS

- ▶ Construction Enclosures
- ▶ Crawl Space Encapsulations
- ▶ Aquaponic Liners
- ▶ Vapor Barriers
- ▶ Vapor Retarders

PRODUCT USE

Vapor Tape has a WVTR of 0.18 perms per ASTM D 833. Typical applications include vapor retarders, covers and liners. Vapor Tape is pressure sensitive, so the bond will strengthen over time. We suggest keeping your tape at room temperature before use.

SIZE AND PACKAGING

Available in a 4” x 210’ roll. This roll is sold individually. Cases include 12 rolls.

PROPERTIES	VALUES
Backing	6.7 mil Polyethylene
Adhesive	3.3 mil Rubber Based Pressure-Sensitive
Color	White
Type	Single Sided
Adhesion Values	35 oz. / in. (to steel)
Perms	0.89 g/(24*100 in ²)
Service Temp.	-40° F to +180° F
Min. Application Temp	50° F
Ideal Storage Temp./Humidity	70° F w/ 40-50 %

Note: To the best of our knowledge, unless otherwise stated, these are typical property values and are intended as guides only, not as specification limits. Chemical resistance, odor transmission, longevity as well as other performance criteria is not implied or given and actual testing must be performed for applicability in specific applications and/or conditions. AMERICOVER, INC. MAKES NO WARRANTIES AS TO THE FITNESS FOR A SPECIFIC USE OR MERCHANTABILITY OF PRODUCTS REFERRED TO, no guarantee of satisfactory results from reliance upon contained information or recommendations and disclaims all liability for resulting loss or damage. Limited Warranty available at www.Americover.com