PRODUCT INFORMATION

MULTI SURFACE PROTECTION FILM

Multi Surface Protection Film is a durable, self-adhering protective film for hard surfaces such as tile, marble, granite, vinyl, VCT, laminates and factory finished hardwood. It's not only great for floor protection, but can be used to prevent damage to most counter tops, tubs, sinks, doors and more. Multi Surface Protection Film is ideal for remodeling, painting, moving, model home tours and even parties.







FEATURES

- Self-adhering film for hard surfaces
- Shields floors from dirt and moisture
- Protects tile, marble, granite, vinyl, laminates ad factory finished hardwood
- Can also prevent damage to tubs and counters
- Reduces clean up time and damage claims

APPLICATIONS

- Construction
- Moving
- Remodeling
- Model Homes
- Drywall
- Painting
- Parties
- Temporary Protection

PRODUCT SPECIFICATIONS

Thickness 3.0 mil nominal

Film Low Density Polyethylene Adhesive Type Formulated Acrylic

Adhesion Level 5-9 oz/in
Tensile Strength 3800 psi
Temperature (Ideal) 70° F

Temperature (Ideal) 70° F Humidity (Ideal) 50% Elongation 470%

Chemical Name Acrylic PSA Tapes

Chemical Family Acrylic PSA Polyethylene Film

Chemical Formula Proprietary
Trade Name Multi Surface
Material Use Surface Protection

AVAILABLE SIZES

MU2450	Green	24" x 50'	1 lb.
FS24200L	Green	24" x 200'	7 lbs.
FS24500	Green	24" x 500'	17 lbs.
FS36250	Green	36" x 250'	13 lbs.
FS36500	Green	36" x 500'	26 lbs.

INSTRUCTIONS

Peel back edge of Multi Surface and begin to unroll. Press down edge at beginning of area to be covered so Multi Surface adheres. Continue rolling onto hard surface are applying pressure and smoothing down the film while doing so. Carefully cut end with a sharp edge. When finished, fold edge of the film back against the roll to use at a later time. Removal: roll up Multi Surface and discard.

HANDLING AND STORAGE

Recommended for hard surfaces like VCT, laminate, and factory finished hardwood floors. Store at room temperature and keep out of direct sunlight exposure. If Multi Surface is stored in extreme conditions (over 95° F or below 40° F) allow product to return to room temperature prior to use. Not recommended for hardwood floors that are not factory finished.

SAFETY

SDS sheets for Surface Shields products available by request.

The information in this document was obtained from sources which we believe reliable. The information is provided without any warranty expressed or implied regarding its correctness. We do not assume responsibility for loss, damage or expense in any way connected with the handling, storage, use or disposal of the product.

© 2015 Surface Shields, Inc. All rights reserved. Product names & attributes trademark of Surface Shields, Inc. where applicable.

5102.70