

PREMIUM RESILIENT TAPE

PRODUCT INFORMATION GUIDE

Application(s):	Our premium resilient tape is a calendered vinyl film with moderate tensile strength, high elongation and good tear strength. This product is recommended for use on any clean dry surface to improve traction under both wet and dry conditions. An excellent choice for bare foot or office environments. Product available in 2 standard colors: Black and Gray. Custom colors also available.
Part Number:	PFX-Series
Adhesive:	Acrylic Adhesive
Carrier:	Vinyl film is calendered and embossed.
Liner:	Poly coated two sides, heavy weight 50g/inch release one side.
Thickness:	0.024" +/- 3%
Tape Application:	Minimum application temperature 10 ⁰ C (50 ⁰ F) Surface must be clean and free from dust, dirt, oil, wax, silicone.
Cleaning:	Clean substrate with a mild soap solution and water, rinse with fresh water.
Shelf Life:	One year from date of purchase when stored at 70 ⁰ F, 50% relative humidity.

Property:	Test Method:	Measurement:
<i>PVC Film</i> Thickness	PSTC-1	0.024" +/- 3%
<i>Acrylic Adhesive</i> Dry Coat Weight		1.50 mils +/- 10%
Adhesion (Steel)		43 oz./ inch (immediate) 53 oz./inch (24 hours) 78 oz./inch (7 days)