

The Nystrom Architectural Access Door is designed with the architect in mind. Constructed with an industry-standard 14 gauge steel door, the updated design provides superior strength and design aesthetics.

- DOOR: 14 gauge cold rolled steel (removable) or 16 gauge T304 stainless steel
- FRAME: 16 gauge cold rolled steel or 16 gauge T304 stainless steel
- HINGE: Concealed spring button
- PAN DEPTH: 1/2"
- FINISH: White powder paint
- OPTIONS: Flanges, Latches, Anchors, Gaskets and Stainless Steel



NTC1212

Features



Anti-flex frame

Screws are inserted through our patent-pending Easy Install Tabs, firmly fitting the door to the wall without flexing the frame.



Painless installation

When mounting screws are not required, quickly and easily install your new panel by bending our patent-pending Easy Install Tabs over the drywall.



Optional stainless steel

The spot free design on the face of the door gives an aesthetically pleasing appearance.

CUSTOM SIZING



N
FLANGE
LATCH
WIDTH
X
HEIGHT
OPTIONS

FLANGE	
T	1" Flange
W	Drywall bead
P	Plaster casing

LATCH	
C	Screwdriver cam latch
L	Key operated cam latch
M	Mortise lock (1-1/8") prep
N	Knurled Knob

STANDARD SIZES (WIDTH & HEIGHT)				
6" x 6"	12" x 24"	18" x 24"	24" x 30"	32" x 32"
8" x 8"	14" x 14"	20" x 30"	24" x 36"	36" x 36"
10" x 10"	16" x 16"	22" x 22"	24" x 48"	36" x 48"
12" x 12"	16" x 20"	22" x 30"	30" x 30"	
12" x 18"	18" x 18"	24" x 24"	30" x 36"	

OPTIONS	
S	T304 Stainless Steel
B	Galvannealed
G	Gasketing
M	Masonry anchors

Custom sizes are available. Rough opening is door size + 1/4".