

# Uninsulated Access Door

The Nystrom U-Series fire-rated, Uninsulated Access Door provides access through openings in fire-rated vertical surfaces.

DOOR: 14 gauge cold rolled steel  
 FRAME: 16 gauge cold rolled steel  
 HINGE: UT: Flush continuous piano  
 UW/UP: Concealed pin  
 FINISH: White powder paint  
 CERTIFICATION: UL listed "B" label for 1-1/2 hrs

FIRE-RATED 

VERTICAL ONLY 

CUSTOM SIZING 

 LISTED



UTK1212

**U**

FLANGE

LATCH

WIDTH

**X**

HEIGHT

OPTIONS

FLANGE	
T	1" Flange
W	Drywall bead
P	Plaster casing

LATCH	
K	Knurled knob / key operated latch bolt
M	Mortise lock (1-1/8") prep

STANDARD SIZES (WIDTH & HEIGHT)			
8" x 8"	16" x 16"	22" x 36"	32" x 32"
10" x 10"	18" x 18"	24" x 24"	36" x 36"
12" x 12"	18" x 24"	24" x 30"	36" x 48"
12" x 18"	20" x 30"	24" x 36"	
12" x 24"	22" x 22"	24" x 48"	
14" x 14"	22" x 30"	30" x 30"	

OPTIONS	
B	Galvannealed
G	Gasketing
M	Masonry anchors
S	T304 Stainless steel

Custom sizes are available. Rough opening is door size + 1/4".

# Oversized Attic Access Door

Nystrom's Oversized Attic Access Door allows access into ceilings when over-sized or double door applications are required. The double leaf design allows objects to clear which may interfere with door openings.

DOOR: 18 gauge bonderized steel  
 FRAME: 16 gauge bonderized steel  
 HINGE: Concealed continuous rod  
 LATCH: 1/4" Allen head key  
 FINISH: White powder paint  
 INSULATION: 1-1/2" non-combustible, high temperature  
 CERTIFICATION: Warnock-Hersey listed for 2 hrs (standard)  
 Warnock-Hersey listed for 3 hrs (with T option)

FIRE-RATED 

CUSTOM SIZING 

 LISTED



FRD3648DW

**FRD**

WIDTH

**X**

HEIGHT

OPTIONS

STANDARD SIZES (WIDTH & HEIGHT)		
36" x 60"	40" x 60"	48" x 60"

OPTIONS	
D	Double door
M	Mortise lock (1-1/8") prep
S	T304 Stainless steel
T	3-Hour rated
C	Ceiling application
W	Wall application

Custom sizes are available. Rough opening is door size.