

Revision Date: 11/18/2016

Approved by: BK

Version: TR-1

PRODUCT SPECIFICATION
PRODUCT ID # : U8132-12060

Self Adhered Treadway

Base Fabric

Weight 3.9 oz/yd² (92 g/m²)
Yarn Polyester
Color Gray, Black
Sealing Self Adhered
Width 12" and 18"

Form Rolls and Cut Pieces
w PET Release Liner

Physical Properties	Units	Test Method	Minimum value	
Thickness	mils	ASTM D751	115	
	mm		2.92	
Weight	oz/yd ²	ASTM D751	70	
	g/m ²		2373	
Tear Strength (Tongue Tear)	lbs	ASTM D751- B	40 (MD)	40 (TD)
	N		178 (MD)	178 (TD)
Breaking Strength (Grab Tensile)	lbs	ASTM D751-A	200 (MD)	200 (TD)
	N		890 (MD)	890 (TD)
Hydrostatic Resistance (Mullen Tester)	psi	ASTM D751-A	400	
	Mpa		2.76	
Adhesion- Ply	lb/in	ASTM D751	15	
	N/25mm		66	
Puncture Resistance (Screw Tip)	lbs	ASTM D751	96	
	N		427	
Dimensional Stability (max)	%	ASTM D1204	1.5%	
Durometer Hardness	Shore A	ASTM D 2240	85	
Peel & Stick Adhesion on Xtrm Ply	lbs/in	RMA SOP	15	
Peel & Stick Seam Strength on Xtrm Ply	lbs/in	RMA SOP	75	
Peel & Stick Adhesion on Metal	lbs/in	RMA SOP	10	
Peel & Stick Seam Strength on Metal	lbs/in	RMA SOP	25	

0

Product Specifications are minimum values, actual results may be higher

We believe this information is the best currently available on the subject. It is provided as a suggestion in any appropriate experimentation you may care to undertake. It is subject to revision as additional knowledge, information and experience are gained. We make no guarantee of results and assume no obligation, warranty or liability whatsoever in connection with this information. In case of conflict between standard and metric specifications, standard shall apply